

16 CFM @ 175 PSI - 8 GALLON AIR COMPRESSOR, GENERATOR WITH HONDA GX390 ENGINE

MODEL: AC138HEG2

COMMERCIAL

SERIES


FEATURES

- **Commercial grade Honda engine** with excellent weight to power ratio that is designed to be used all day, everyday.
- **Electric start system** with battery included.
- **Belt drive** system keeps the pump RPM low and running cooler to extend its performance and life span.
- **Heavy-duty, two-stage splash lubricated pump** with cast iron cylinders, accessible valves, and bearings on both end of the crank shaft to maximize longevity.
- **Pilot unloader valve** is an USA Conrader set to cut in at 140 PSI and cut out at 175 PSI.
- **Generator** is powered by the Honda engine and can be used at the same time as the compressor.
- **Twin 4-gallon tanks** are powder coated for added durability and each one has a ball valve tank drain port. Pre-drilled holes in the stabilizing brackets for mounting it into a truck or trailer.
- **Removable saddle** so the user is able to separate the engine/pump from the tank for specialized set ups.



Scan the QR code with your mobile device and discover more about this BE air compressor.

GENERATOR OUTLETS



120V 20A

ENGINE

MODEL: **HONDA GX390**
 TYPE: **AIR COOLED, 4-STROKE OHV**
 DISPLACEMENT: **389CC**
 FUEL TYPE: **86 OCTANE, UP TO 10% ETHANOL**
 OIL TYPE: **SAE 10W30**

FRAME

TANK SIZE: **8 GALLONS**
 MATERIAL: **POWDER COATED STEEL**
 TANK DRAIN: **TWIST VALVE**
 WHEELS: **12" FLAT FREE**

GENERATOR SPECS

MAX WATTS: **4,000**
 RUNNING WATTS: **3,500**
 VOLTAGE: **120**


PUMP SPECS

TYPE: **RECIPROCATING**
 PART NUMBER: **42.005.018**
 MAX PSI: **175**
 STAGE: **TWO**
 OIL TYPE: **30W NON-DETERGENT**
 DUTY CYCLE: **80%**
 RPM: **975**
 AIR FILTER: **1" NPT PORT SIZE**
 PART NUMBER: **42.005.052**

BOXED SIZE

LxWxH: **50" x 32" x 48"**
 WEIGHT: **550 LBS**

UNIT SIZE



UNIT WEIGHT: **490 LBS**

WARRANTY

ENGINE: **3 YEARS**
 PUMP: **2 YEARS**
 UPC: **777897292602**

05-2021